

1 Identification

Product identifier

Product name: 1,2-Propanediol monomethyl ether acetate

Stock number: 43375

CAS Number:

108-65-6

EC number:

203-603-9

Index number:

607-195-00-7

Relevant identified uses of the substance or mixture and uses advised against.

Identified use: SU24 Scientific research and development

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Alfa Aesar

Thermo Fisher Scientific Chemicals, Inc.

30 Bond Street

Ward Hill, MA 01835-8099

Tel: 800-343-0660

Fax: 800-322-4757

Email: tech@alfa.com

www.alfa.com

Information Department: Health, Safety and Environmental Department

Emergency telephone number:

During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660. After normal business hours, call Carechem 24 at (866) 928-0789.

2 Hazard(s) identification

Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

Hazards not otherwise classified No information known.

Label elements

GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)

Hazard pictograms



GHS02

Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P233 Keep container tightly closed.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS classification

B3 - Combustible liquid



Classification system

HMIS ratings (scale 0-4)

(Hazardous Materials Identification System)

HEALTH 1 Health (acute effects) = 1

FIRE 2 Flammability = 2

REACTIVITY 1 Physical Hazard = 1

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Substances

CAS# Description:

108-65-6 1,2-Propanediol monomethyl ether acetate

Identification number(s):

EC number: 203-603-9

Index number: 607-195-00-7

4 First-aid measures

Description of first aid measures

After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm.

Product name: 1,2-Propanediol monomethyl ether acetate

(Contd. of page 1)

Seek immediate medical advice.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

Seek immediate medical advice.

After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing Seek medical treatment.

Information for doctor

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents Carbon dioxide, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture

If this product is involved in a fire, the following can be released:

Carbon monoxide and carbon dioxide

Advice for firefighters

Protective equipment:

Wear self-contained respirator.

Wear fully protective impervious suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

Environmental precautions: Do not allow product to reach sewage system or any water course.

Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Prevention of secondary hazards: Keep away from ignition sources.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling

Precautions for safe handling

Keep container tightly sealed.

Store in cool, dry place in tightly closed containers.

Ensure good ventilation at the workplace.

Information about protection against explosions and fires:

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away.

Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Store away from oxidizing agents.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters

Components with limit values that require monitoring at the workplace:

108-65-6 1,2-Propanediol monomethyl ether acetate (100.0%)

WEEL (USA) Long-term value: 50 ppm

EL (Canada) Short-term value: 75 ppm

Long-term value: 50 ppm

EV (Canada) Long-term value: 270 mg/m³, 50 ppm

Additional information: No data

Exposure controls

Personal protective equipment

General protective and hygienic measures

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Maintain an ergonomically appropriate working environment.

Breathing equipment: Use suitable respirator when high concentrations are present.

Recommended filter device for short term use:

Use a respirator with multi-purpose combination (US) or type ABEK (EN 14387) as a backup to engineering controls. Risk assessment should be performed to determine if air-purifying respirators are appropriate. Only use equipment tested and approved under appropriate government standards such as NIOSH (USA) or CEN (EU).

Protection of hands:

Impervious gloves

Check protective gloves prior to each use for their proper condition.

The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Material of gloves Butyl rubber, BR

Penetration time of glove material (in minutes) >480

Glove thickness 0.3 mm

Eye protection: Safety glasses

Body protection: Protective work clothing.

Product name: 1,2-Propanediol monomethyl ether acetate

(Contd. of page 2)

9 Physical and chemical properties**Information on basic physical and chemical properties****General Information****Appearance:**

Form: Liquid
Odor: Ester-like
Odor threshold: Not determined.

pH-value (200 g/l) at 20 °C (68 °F):

4

Change in condition

Melting point/Melting range: -67 °C (-89 °F)
Boiling point/Boiling range: 145-146 °C (293-295 °F)
Sublimation temperature / start: Not determined

Flash point: 43 °C (109 °F)
Flammability (solid, gaseous) Not determined.
Ignition temperature: 315 °C (599 °F)
Decomposition temperature: Not determined
Auto igniting: Not determined.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures is possible.**Explosion limits:**

Lower: 1.5 Vol %
Upper: 10.8 Vol %
Vapor pressure at 20 °C (68 °F): 3.37 hPa (3 mm Hg)
Density at 20 °C (68 °F): 0.968 g/cm³ (8.078 lbs/gal)
Relative density Not determined.
Vapor density Not determined.
Evaporation rate Not determined.

Solubility in / Miscibility with

Water at 20 °C (68 °F): 220 g/l
Partition coefficient (n-octanol/water): Not determined.

Viscosity:

dynamic at 20 °C (68 °F): 1.2 mPas
kinematic: Not determined.

Other information No further relevant information available.**10 Stability and reactivity****Reactivity** No information known.**Chemical stability** Stable under recommended storage conditions.**Thermal decomposition / conditions to be avoided:** Decomposition will not occur if used and stored according to specifications.**Possibility of hazardous reactions** Reacts with strong oxidizing agents**Conditions to avoid** No further relevant information available.**Incompatible materials:** Oxidizing agents**Hazardous decomposition products:** Carbon monoxide and carbon dioxide**11 Toxicological information****Information on toxicological effects****Acute toxicity:** The Registry of Toxic Effects of Chemical Substances (RTECS) contains acute toxicity data for this substance.**LD/LC50 values that are relevant for classification:** No data**Skin irritation or corrosion:** May cause irritation**Eye irritation or corrosion:** May cause irritation**Sensitization:** No sensitizing effects known.**Germ cell mutagenicity:** No effects known.**Carcinogenicity:** No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.**Reproductive toxicity:** No effects known.**Specific target organ system toxicity - repeated exposure:** No effects known.**Specific target organ system toxicity - single exposure:** No effects known.**Aspiration hazard:** No effects known.**Subacute to chronic toxicity:** The Registry of Toxic Effects of Chemical Substances (RTECS) contains multiple dose toxicity data for this substance.**Additional toxicological information:** To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.**Carcinogenic categories****OSHA-Ca (Occupational Safety & Health Administration)** Substance is not listed.**12 Ecological information****Toxicity****Aquatic toxicity:** No further relevant information available.**Persistence and degradability** No further relevant information available.**Bioaccumulative potential** No further relevant information available.**Mobility in soil** No further relevant information available.**Additional ecological information:****General notes:** Avoid transfer into the environment.**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**Other adverse effects** No further relevant information available.**13 Disposal considerations****Waste treatment methods****Recommendation** Consult state, local or national regulations to ensure proper disposal.**Uncleaned packagings:****Recommendation:** Disposal must be made according to official regulations.**14 Transport information****UN-Number**
DOT, IMDG, IATA

UN3272

(Contd. on page 4)
USA

Product name: 1,2-Propanediol monomethyl ether acetate

(Contd. of page 3)

UN proper shipping name

DOT

IMDG, IATA

Esters, n.o.s. (1,2-Propanediol monomethyl ether acetate)
ESTERS, N.O.S. (1,2-Propanediol monomethyl ether acetate)

Transport hazard class(es)

DOT



Class

Label

Class

Label

IMDG, IATA

3 Flammable liquids.
3
3 (F1) Flammable liquids
3

Class

Label

3 Flammable liquids.
3

Packing group

DOT, IMDG, IATA

III

Environmental hazards:

Not applicable.

Special precautions for user

Warning: Flammable liquids
F-E, S-D

EMS Number:

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional information:

DOT

Marine Pollutant (DOT):

No

UN "Model Regulation":

UN3272, Esters, n.o.s. (1,2-Propanediol monomethyl ether acetate), 3, III

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS)

Hazard pictograms



GHS02

Signal word Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P233 Keep container tightly closed.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.

All components of this product are listed on the Canadian Domestic Substances List (DSL).

SARA Section 313 (specific toxic chemical listings) Substance is not listed.

California Proposition 65

Prop 65 - Chemicals known to cause cancer Substance is not listed.

Prop 65 - Developmental toxicity Substance is not listed.

Prop 65 - Developmental toxicity, female Substance is not listed.

Prop 65 - Developmental toxicity, male Substance is not listed.

Information about limitation of use: For use only by technically qualified individuals.

Other regulations, limitations and prohibitive regulations

Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.

The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing SDS: Global Marketing Department

Date of preparation / last revision 10/27/2016 / -

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

LC50: Lethal concentration, 50 percent

(Contd. on page 5)

USA

Product name: 1,2-Propanediol monomethyl ether acetate

LD50: Lethal dose, 50 percent
vPvB: very Persistent and very Bioaccumulative
ACGIH: American Conference of Governmental Industrial Hygienists (USA)
OSHA: Occupational Safety and Health Administration (USA)
NTP: National Toxicology Program (USA)
IARC: International Agency for Research on Cancer
EPA: Environmental Protection Agency (USA)
Flam. Liq. 3: Flammable liquids, Hazard Category 3

(Contd. of page 4)