

SAFETY DATA SHEET

Version 4.11
Revision Date 05/23/2016
Print Date 10/17/2019

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : Lithium hexafluoroarsenate(V)

Product Number : 308315
Brand : Aldrich
Index-No. : 033-002-00-5

CAS-No. : 29935-35-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich
3050 Spruce Street
SAINT LOUIS MO 63103
USA

Telephone : +1 800-325-5832
Fax : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887 (CHEMTREC)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 3), H301
Acute toxicity, Inhalation (Category 3), H331
Acute aquatic toxicity (Category 1), H400
Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word : Danger

Hazard statement(s)

H301 + H331 : Toxic if swallowed or if inhaled
H410 : Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P261 : Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 : Wash skin thoroughly after handling.
P270 : Do not eat, drink or smoke when using this product.
P271 : Use only outdoors or in a well-ventilated area.
P273 : Avoid release to the environment.
P301 + P310 + P330 : IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse

P304 + P340 + P311	mouth. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Formula	: AsF ₆ Li
Molecular weight	: 195.85 g/mol
CAS-No.	: 29935-35-1
EC-No.	: 249-963-0
Index-No.	: 033-002-00-5

Hazardous components

Component	Classification	Concentration
Lithium hexafluoroarsenate(V)		
	Acute Tox. 3; Aquatic Acute 1; Aquatic Chronic 1; H301 + H331, H410	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. Hydrofluoric (HF) acid burns require immediate and specialized first aid and medical treatment. Symptoms may be delayed up to 24 hours depending on the concentration of HF. After decontamination with water, further damage can occur due to penetration/absorption of the fluoride ion. Treatment should be directed toward binding the fluoride ion as well as the effects of exposure. Skin exposures can be treated with a 2.5% calcium gluconate gel repeated until burning ceases. More serious skin exposures may require subcutaneous calcium gluconate except for digital areas unless the physician is experienced in this technique, due to the potential for tissue injury from increased pressure. Absorption can readily occur through the subungual areas and should be considered when undergoing decontamination. Prevention of absorption of the fluoride ion in cases of ingestion can be obtained by giving milk, chewable calcium carbonate tablets or Milk of Magnesia to conscious victims. Conditions such as hypocalcemia, hypomagnesemia and cardiac arrhythmias should be monitored for, since they can occur after exposure.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician. First treatment with calcium gluconate paste.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust.
For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.
Provide appropriate exhaust ventilation at places where dust is formed.
For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Keep in a dry place.

Storage class (TRGS 510): Non-combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
	Remarks	Substance listed; for more information see OSHA document 1910.1018		
Lithium hexafluoroarsenate(V)	29935-35-1	TWA	0.010000 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
		Lung cancer Substances for which there is a Biological Exposure Index or Indices		

		(see BEI® section) Confirmed human carcinogen varies		
		PEL	0.010000 mg/m3	OSHA Specifically Regulated Chemicals/Carcinogens
		1910.1018 This section applies to all occupational exposures to inorganic arsenic except that this section does not apply to employee exposures in agriculture or resulting from pesticide application, the treatment of wood with preservatives or the utilization of arsenically preserved wood. OSHA specifically regulated carcinogen		
		C	0.002000 mg/m3	USA. NIOSH Recommended Exposure Limits
		Potential Occupational Carcinogen OSHA considers 'Inorganic Arsenic' to mean copper acetoarsenite & all inorganic compounds containing arsenic except ARSINE. See Appendix A 15 minute ceiling value		
		Substance listed; for more information see OSHA document 1910.1018		
		TWA	0.01 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
		Lung cancer Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Confirmed human carcinogen varies		
		PEL	0.01 mg/m3	OSHA Specifically Regulated Chemicals/Carcinogens
		1910.1018 This section applies to all occupational exposures to inorganic arsenic except that this section does not apply to employee exposures in agriculture or resulting from pesticide application, the treatment of wood with preservatives or the utilization of arsenically preserved wood. OSHA specifically regulated carcinogen		
		C	0.002 mg/m3	USA. NIOSH Recommended Exposure Limits
		Potential Occupational Carcinogen OSHA considers 'Inorganic Arsenic' to mean copper acetoarsenite & all inorganic compounds containing arsenic except ARSINE. See Appendix A 15 minute ceiling value		
		PEL	0.01 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		see Section 5214		

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N99 (US) or type P2 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

a) Appearance	Form: powder Colour: white
b) Odour	No data available
c) Odour Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	No data available
f) Initial boiling point and boiling range	No data available
g) Flash point	Not applicable
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	No data available
k) Vapour pressure	No data available
l) Vapour density	No data available
m) Relative density	No data available
n) Water solubility	No data available
o) Partition coefficient: n-octanol/water	No data available
p) Auto-ignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

No data available

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

No data available

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Hydrogen fluoride, Lithium oxides, Arsenic oxides

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

This is or contains a component that has been reported to be carcinogenic based on its IARC, OSHA, ACGIH, NTP, or EPA classification.

IARC: 1 - Group 1: Carcinogenic to humans (Lithium hexafluoroarsenate(V))

1 - Group 1: Carcinogenic to humans (Lithium hexafluoroarsenate(V))

NTP: Known to be human carcinogen (Lithium hexafluoroarsenate(V))

OSHA: OSHA specifically regulated carcinogen (Lithium hexafluoroarsenate(V))

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: Not available

Fluoride ion can reduce serum calcium levels possibly causing fatal hypocalcemia.

Absorption into the body leads to the formation of methemoglobin which in sufficient concentration causes cyanosis. Onset may be delayed 2 to 4 hours or longer.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

12. ECOLOGICAL INFORMATION**12.1 Toxicity**

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods****Product**

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION**DOT (US)**

UN number: 1557 Class: 6.1 Packing group: II
Proper shipping name: Arsenic compounds, solid, n.o.s. (Lithium hexafluoroarsenate(V))
Reportable Quantity (RQ):

Poison Inhalation Hazard: No

IMDG

UN number: 1557 Class: 6.1 Packing group: II EMS-No: F-A, S-A
Proper shipping name: ARSENIC COMPOUND, SOLID, N.O.S. (Lithium hexafluoroarsenate(V))
Marine pollutant: yes

IATA

UN number: 1557 Class: 6.1 Packing group: II
Proper shipping name: Arsenic compound, solid, n.o.s. (Lithium hexafluoroarsenate(V))

15. REGULATORY INFORMATION**SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
Lithium hexafluoroarsenate(V)	29935-35-1	2007-03-01

SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components

	CAS-No.	Revision Date
Lithium hexafluoroarsenate(V)	29935-35-1	2007-03-01

New Jersey Right To Know Components

	CAS-No.	Revision Date
Lithium hexafluoroarsenate(V)	29935-35-1	2007-03-01

California Prop. 65 Components

WARNING! This product contains a chemical known to the State of California to cause cancer.

	CAS-No.	Revision Date
Lithium hexafluoroarsenate(V)	29935-35-1	2007-09-28

16. OTHER INFORMATION**Full text of H-Statements referred to under sections 2 and 3.**

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
H301	Toxic if swallowed.
H301 + H331	Toxic if swallowed or if inhaled
H331	Toxic if inhaled.

HMIS Rating

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	0

NFPA Rating

Health hazard:	2
Fire Hazard:	0
Reactivity Hazard:	0

Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation
Product Safety – Americas Region
1-800-521-8956

Version: 4.11

Revision Date: 05/23/2016

Print Date: 10/17/2019