

Safety Data Sheet per OSHA HazCom 2012

Page 1/5 Printing date 11/24/2015 Reviewed on 12/11/2014

## 1 Identification

Product identifier

Product name: Petroleum ether 35/60

Stock number: 38985 CAS Number: **EC** number: 232-453-7 Index number:

649-263-00-9 Relevant identified uses of the substance or mixture and uses advised against.

Identified use: SU24 Scientific research and development

Details of the supplier of the safety data sheet

Manufacturer/Supplier: Alfa Aesar

Alla Aesai Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street Ward Hill, MA 01835-8099 Tel: 800-343-0660 Fax: 800-322-4757 Email: tech@alfa.com www.alfa.com

www.ana.com I**nformation Department:** Health, Safety and Environmental Department **Emergency telephone number:** During normal business hours (Monday-Friday, 8am-7pm EST), call (800) 343-0660. After normal business hours, call Carechem 24 at (866) 928-0789.

#### 2 Hazard(s) identification

Classification of the substance or mixture in accordance with 29 CFR 1910 (OSHA HCS)



GHS02 Flame

Flam. Liq. 1 H224 Extremely flammable liquid and vapour.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

H350 May cause cancer. Carc. 1B

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Hazards not otherwise classified No information known.

GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS) Hazard pictograms





**GHS02 GHS08** 

# Signal word Danger Hazard statements

H224 Extremely flammable liquid and vapour. H340 May cause genetic defects. H350 May cause cancer.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

Precautionary statements
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor/...
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P405 Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
WHMIS classification

WHMIS classification

B2 - Flammable liquid
D2A - Very toxic material causing other toxic effects



Classification system

HMIS ratings (scale 0-4) (Hazardous Materials Identification System)



Health (acute effects) = 1 Flammability = 4

Flammability = 4

ACTIVITY Physical Hazard = 1

Other hazards Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

## 3 Composition/information on ingredients

Chemical characterization: Substances CAS# Description: 8032-32-4 Petroleum ether 35/60 Identification number(s): EC number: 232-453-7

(Contd. on page 2)

## Product name: Petroleum ether 35/60

(Contd. of page 1) Index number: 649-263-00-9

## 4 First-aid measures

#### Description of first aid measures

After inhalation Supply fresh air. If required, provide artificial respiration. Keep patient warm. Seek immediate medical advice.

After skin contact
Immediately wash with water and soap and rinse thoroughly.
Seek immediate medical advice.
After eye contact Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing Seek medical treatment.
Information for doctor

Most important symptoms and effects, both acute and delayed No further relevant information average.

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents Carbon dioxide, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Special hazards arising from the substance or mixture

If this product is involved in a fire, the following can be released:

This product is invoved in a file, the Carbon monoxide and carbon dioxide Advice for firefighters
Protective equipment:
Wear self-contained respirator.
Wear fully protective impervious suit.

## 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
Environmental precautions: Do not allow material to be released to the environment without proper governmental permits.
Methods and material for containment and cleaning up:
Keep away from ignition sources.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to section 13.
Ensure adequate ventilation.

Ensure adequate ventilation.

Prevention of secondary hazards: Keep away from ignition sources.

Reference to other sections
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

## 7 Handling and storage

Handling Precautions for safe handling

Precautions for safe handling
Keep container tightly sealed.
Store in cool, dry place in tightly closed containers.
Keep away from heat and direct sunlight.
Ensure good ventilation at the workplace.
Open and handle container with care.
Information about protection against explosions and fires:
Protect against electrostatic charges.
Fumes can combine with air to form an explosive mixture.
Keen intition sources away.

Keep ignition sources away.

## Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles: Store in a cool location.
Information about storage in one common storage facility: Store away from oxidizing agents.
Further information about storage conditions:

Keep container tightly sealed.
Store in cool, dry conditions in well sealed containers.
Protect from heat and direct sunlight.
Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

Additional information about design of technical systems:
Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Control parameters

## Components with limit values that require monitoring at the workplace:

8032-32-4 Petroleum ether 35/60 (100.0%)

REL (USA)

Long-term value: 350 mg/m³ Ceiling limit value: 1800\* mg/m³ \*15-min

TLV Withdrawn - refer to Appendix H

TLV (USA) EL (Canada) reciprocal calculation method - see OHS G5.48-12

Additional information: No data

Exposure controls

Exposure controls
Personal protective equipment
General protective and hygienic measures
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Remove all soiled and contaminated clothing immediately.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Maintain an ergonomically appropriate working environment.

(Contd. on page 3)

(Contd. of page 2)

## Product name: Petroleum ether 35/60

Liauid

Colorless Petroleum-like Not determined

Not determined

Not determined

-49 °C (-56 °F) Not applicable. 250 °C (482 °F) Not determined

Not determined.

Not determined

Not determined Not determined

8 Vol % 350 hPa (263 mm Hg) 0.64 g/cm³ (5.341 lbs/gal) Not determined.

0.6 Vol %

Not determined 35-60 °C (95-140 °F)

Breathing equipment: Use suitable respirator when high concentrations are present.

Recommended filter device for short term use:

Use a respirator with organic vapor/acid gas cartridges as a backup to engineering controls. Risk assessment should be performed to determine if air-purifying respirators are appropriate. Only use equipment tested and approved under appropriate government standards such as NIOSH (USA) or CEN (EU). Protection of hands:

Product is not explosive. However, formation of explosive air/vapor mixtures is possible.

Impervious gloves
Check protection of names:
Impervious gloves
Check protective gloves prior to each use for their proper condition.
The selection of suitable gloves not only depends on the material, but also on quality. Quality will vary from manufacturer to manufacturer.

Material of gloves Nitrile rubber, NBR
Penetration time of glove material (in minutes) 480
Glove thickness 0.4 mm
Eye protection: Safety glasses
Body protection: Protective work clothing.

9 Physical and chemical properties

Information on basic physical and chemical properties General Information

Appearance: Form:

Color: Odor: Odor threshold:

pH-value:

Change in condition Melting point/Melting range: Boiling point/Boiling range: Sublimation temperature / start:

Flash point: Flammability (solid, gaseous) Ignition temperature: Decomposition temperature:

Auto igniting: Danger of explosion: Explosion limits:

Lower:
Lower:
Upper:
Vapor pressure at 20 °C (68 °F):
Density at 20 °C (68 °F):
Relative density

Vapor density Evaporation rate
Solubility in / Miscibility with
Water at 20 °C (68 °F):
Water of Coefficient (n-octanol/water): Not determined.

Water of Coefficient (n-octanol/water): Not determined.

Viscosity:

dynamic: kinematic: Other information

10 Stability and reactivity

Reactivity No information known.

Chemical stability Stable under recommended storage conditions.

Thermal decomposition / conditions to be avoided: Decomposition will not occur if used and stored according to specifications.

Possibility of hazardous reactions Reacts with strong oxidizing agents

Conditions to avoid No further relevant information available.

Incompatible materials: Oxidizing agents

Hazardous decomposition products: Carbon monoxide and carbon dioxide

No further relevant information available

## 11 Toxicological information

Information on toxicological effects
Acute toxicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains acute toxicity data for this substance.
LD/LC50 values that are relevant for classification:

Inhalative LC50/4H 3400 ppm/4H (rat)

Skin irritation or corrosion: Irritant to skin and mucous membranes. Eye irritation or corrosion: Irritating effect.

Sensitization: No sensitizing effects known. Germ cell mutagenicity: May cause genetic defects.

Germ cell mutagenicity: May cause genetic defects.
Carcinogenicity:
May cause cancer.
ACGIH A3: Animal carcinogen: Agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histologic type(s), or by mechanism(s) not considered relevant to worker exposure. Available epidemologic studies do not confirm an increased risk of cancer in exposed humans. Available evidence suggests that the agent is not likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure. Reproductive toxicity: The Registry of Toxic Effects of Chemical Substances (RTECS) contains reproductive data for this substance.
Specific target organ system toxicity - repeated exposure: No effects known.
Specific target organ system toxicity - single exposure: No effects known.
Aspiration hazard: May be fatal if swallowed and enters airways.
Subacute to chronic toxicity: No effects known.
Additional toxicological information: To the best of our knowledge the acute and chronic toxicity of this substance is not fully known.

## 12 Ecological information

**Toxicity** 

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

(Contd. on page 4)

(Contd. of page 3)

## Product name: Petroleum ether 35/60

Additional ecological information:
General notes:
Do not allow product to reach ground water, water course or sewage system.
Do not allow material to be released to the environment without proper governmental permits.
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Avoid transfer into the environment.
Results of PBT and vPvB assessment
PBT: Not applicable

PBT: Not applicable. vPvB: Not applicable

Other adverse effects No further relevant information available.

#### 13 Disposal considerations

Waste treatment methods

Recommendation Consult state, local or national regulations to ensure proper disposal. Uncleaned packagings: Recommendation: Disposal must be made according to official regulations.

14	Transport	information
17	IIalisbull	IIIIOIIIIauoii

UN-Number DOT, IMDG, IATA UN1268

UN proper shipping name DOT

Petroleum distillates, n.o.s. PETROLEUM DISTILLATES, N.O.S. IMDG, IATA

## Transport hazard class(es)

DOT



Class 3 Flammable liquids. Label Class (F1) Flammable liquids Label IMDG, IATA



Class 3 Flammable liquids. Label

Packing group DOT, IMDG, IATA

Environmental hazards: Not applicable.

Special precautions for user Warning: Flammable liquids

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

Transport/Additional information:

Marine Pollutant (DOT): No

UN "Model Regulation": UN1268, Petroleum distillates, n.o.s., 3, I

## 15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture GHS label elements The product is classified and labeled in accordance with 29 CFR 1910 (OSHA HCS) Hazard pictograms





GHS02 GHS08

Signal word Danger Hazard statements

H224 Extremely flammable liquid and vapour. H340 May cause genetic defects. H350 May cause cancer. H304 May be fatal if swallowed and enters airways. Precautionary statements

Precautionary statements
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor/...
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P405 Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
P401 Dispose of contents/container in accordance with local/regional/national/international regulations.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations

All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.

All components of this product are listed on the Canadian Domestic Substances List (DSL).

SARA Section 313 (specific toxic chemical listings) Substance is not listed.

California Proposition 65

Prop 65 - Chemicals known to cause cancer Substance is not listed.

Prop 65 - Developmental toxicity Substance is not listed.

Prop 65 - Developmental toxicity, female Substance is not listed.

Prop 65 - Developmental toxicity, male Substance is not listed.

Information about limitation of use:

Workers are not allowed to be exposed to this hazardous material. Exceptions can be made by the authorities in certain cases.

For use only by technically qualified individuals.

(Contd. on page 5)

## Product name: Petroleum ether 35/60

(Contd. of page 4)

Other regulations, limitations and prohibitive regulations
Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No. 1907/2006. Substance is not listed.
The conditions of restrictions according to Article 67 and Annex XVII of the Regulation (EC) No 1907/2006 (REACH) for the manufacturing, placing on the market and use must be observed.

Substance is not listed.

Annex XIV of the REACH Regulations (requiring Authorisation for use) Substance is not listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgement of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user. Conformance with this Material Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Department issuing SDS: Global Marketing Department
Date of preparation / last revision 11/24/2015 / Abbreviations and acronyms:

RID: Réglement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IGAO: International Civil Aviation Organization
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials Information System (Canada)
LC50: Lethal concentration, 50 percent
LPGS: Lethal dose, 50 percent